


Alimac General Purpose Carry C105 S



C105-S is the Alimac go-to choice for general-purpose traditional Carry Handle applications.

Made of an in-house extruded Mono-oriented Polypropylene (MOPP) backing coated with a specially formulated hot melt adhesive, C105-S is suitable for a large variety of post-oven carrying automatic applications.

Specifically, this carry handle tape offers excellent performances:

- Over a broad range of machine application technology and speed
- With a large variety of plastic – based shrink film materials including
 - o Polyethylene
 - o Polypropylene
 - o Polyester

C105-S guarantees a Carrying capacity up to 12 kg (26 lbs) when applied according to the TDS recommended temperature ranges.

By applying a C105-S carry handle can allow a significant shrink film thickness reduction without compromising the package integrity, contributing to reduce the secondary packaging plastic content.

Depending on the material characteristics and on the application speed, C105-S can also be suitable for Paperboard (printed and unprinted) surfaces.

Technical Data

Product Name	Tape Structure (Backing / Adhesive)	Thickness (µ)	Adhesion to Steel / PE (N/25 mm)	Tensile Strength (N/25 mm)	Elongation at Break (%)	Color	Width available (mm)	Length (m)
General Purpose Carry								
C105-S	MOPP / Hot Melt	70	Steel 10 PE 5	350	30	Transparent	23 25 30 37,5	7000 5000 / 6500 5000 3500

Alimac S.r.l.

Via E. Toti 3,
Gerenzano (VA), Italy

PH: + 39 02 9670 2823

customeroperations.it@alimacgroup.com

www.alimacgroup.com

Alimac Iberia s.l.u.

Travessera de Gràcia, 73,
Sarrià-Sant Gervasi,
Barcelona, Spain

PH: +34 93 2385943

customeroperations.es@alimacgroup.com

Alimac Deutschland GmbH

Am Busskolk 9,
Bocholt, Germany

PH: + 49 (0) 2871 238120

customeroperations.de@alimacgroup.com