

C12550 FA

Product description

C12550 FA Hot Melt tape shows technical characteristics suitable for adhesive handle preparation for high adhesion or frozen application. The elevated resistance of the PET film against high temperatures permits the use of this adhesive tape in shrink-ovens without deformation or degradation of the product characteristics.

Technical properties

Backing tape	PET
Color	transparent

Adhesion on PE	5	N/25 mm	AFERA 5001
Adhesion on steel	10	N/25 mm	AFERA 5001
Elongation	130	%	AFERA 5004
Tensile strenght	200	N/25 mm	AFERA 5004
Thickness	50	µm	AFERA 5006
Total thickness	70	µm	AFERA 5006

Storage conditions

Recomended temperature	10-40 °C
Humidity	20-80% RH
Shelf life (months)	12

Available sizes

25X3000

Other sizes may be evaluated upon request.

The above mentioned information are extrapolated from typical production data and not constitute a warranty for the results of the applications.

Alimac S.r.l.

Via E. Toti 3,
Gerenzano (VA), Italy

PH: + 39 02 9670 2823

customeroperations.it@alimacgroup.com

Alimac Iberia s.l.u.

Travessera de Gràcia, 73,
Sarrià-Sant Gervasi,
Barcelona, Spain

PH: +34 93 2385943

customeroperations.es@alimacgroup.com

Alimac Deutschland GmbH

Am Busskolk 9,
Bocholt, Germany

PH: + 49 (0) 2871 238120

customeroperations.de@alimacgroup.com