

# C12050

## Product description

C12050 is a handle tape designed for high temperature applications .

## Technical properties

|              |             |
|--------------|-------------|
| Backing tape | PET         |
| Color        | Transparent |

|                   |     |         |            |
|-------------------|-----|---------|------------|
| Adhesion on PE    | 5   | N/25 mm | AFERA 5001 |
| Adhesion on steel | 8   | N/25 mm | AFERA 5001 |
| Elongation        | 130 | %       | AFERA 5004 |
| Tensile strenght  | 200 | N/25 mm | AFERA 5004 |
| Thickness         | 50  | µm      | AFERA 5006 |
| Total thickness   | 66  | µm      | AFERA 5006 |

## Storage conditions

|                        |           |
|------------------------|-----------|
| Recomended temperature | 10-40 °C  |
| Humidity               | 20-80% RH |
| Shelf life (months)    | 12        |

## Available sizes

25X800

*Other sizes may be evaluated upon request.*

*The above mentioned information are extrapolated from typical production data and not constitute a warranty for the results of the applications.*

Alimac S.r.l.  
Via E. Toti 3,  
Gerenzano (VA), Italy

PH: + 39 02 9670 2823  
[customeroperations.it@alimacgroup.com](mailto:customeroperations.it@alimacgroup.com)

Alimac Iberia s.l.u.  
C/Travessera de Gracia,  
73-79 3º 3ª 08006 ,  
Barcelona, Spain

PH: +34 93 2385943  
[customeroperations.es@alimacgroup.com](mailto:customeroperations.es@alimacgroup.com)

Alimac Deutschland GmbH  
Am Busskolk 9,  
Bocholt, Germany

PH: + 49 (0) 2871 238120  
[customeroperations.de@alimacgroup.com](mailto:customeroperations.de@alimacgroup.com)

[www.alimacgroup.com](http://www.alimacgroup.com)

Revision date: 01/04/2025