

C105 FA UV

Product description

The C105 FA UV tape exhibits technical characteristics suitable for preparing adhesive handles for heavy packages when high adhesion is required. It is particularly resistant to UV rays.

Technical properties

Backing tape	MOPP
Color	transparent

Adhesion on PE	11	N/25 mm	AFERA 5001
Adhesion on steel	18	N/25 mm	AFERA 5001
Elongation	30	%	AFERA 5004
Tensile strenght	350	N/25 mm	AFERA 5004
Thickness	50	µm	AFERA 5006
Total thickness	80	µm	AFERA 5006

Storage conditions

Recomended temperature	10-40 °C
Humidity	20-80% RH
Shelf life (months)	12

Available sizes

25X6000, 30X5000

Other sizes may be evaluated upon request.

The above mentioned information are extrapolated from typical production data and not constitute a warranty for the results of the applications.

Alimac S.r.l.

Via E. Toti 3,
Gerenzano (VA), Italy

PH: + 39 02 9670 2823

customeroperations.it@alimacgroup.com

Alimac Iberia s.l.u.

Travessera de Gràcia, 73,
Sarrià-Sant Gervasi,
Barcelona, Spain

PH: +34 93 2385943

customeroperations.es@alimacgroup.com

Alimac Deutschland GmbH

Am Busskolk 9,
Bocholt, Germany

PH: + 49 (0) 2871 238120

customeroperations.de@alimacgroup.com

www.alimacgroup.com

Revision date: 01/04/2025