

C105 FV UV

Product description

C105 FV-UV Handle Tape is the perfect solution for obtaining adhesive handles for transporting heavy and bulky packages. Thanks to a combination of suitable raw materials, it is particularly resistant to UV radiation. With high adhesion on the shrink PE film, it offers special mechanical resistance and inertia to oxidizing agents. Made of MOPP polypropylene material, it guarantees durability and reliability.

Technical properties

Backing tape	MOPP
Color	transparent

Adhesion on PE	5	N/25 mm	AFERA 5001
Adhesion on steel	10	N/25 mm	AFERA 5001
Elongation	30	%	AFERA 5004
Tensile strenght	380	N/25 mm	AFERA 5004
Thickness	55	µm	AFERA 5006
Total thickness	77	µm	AFERA 5006

Storage conditions

Recomended temperature	10-40 °C
Humidity	20-80% RH
Shelf life (months)	12

Available sizes

37,5X3000

Other sizes may be evaluated upon request.

The above mentioned information are extrapolated from typical production data and not constitute a warranty for the results of the applications

Alimac S.r.l.

Via E. Toti 3,
Gerenzano (VA), Italy

PH: + 39 02 9670 2823

customeroperations.it@alimacgroup.com

Alimac Iberia s.l.u.

Travessera de Gràcia, 73,
Sarrià-Sant Gervasi,
Barcelona, Spain

PH: +34 93 2385943

customeroperations.es@alimacgroup.com

Alimac Deutschland GmbH

Am Busskolk 9,
Bocholt, Germany

PH: + 49 (0) 2871 238120

customeroperations.de@alimacgroup.com

www.alimacgroup.com

Revision date: 01/04/2025