

C105 FA UV

Product description

C105 FA-UV Carry Handle Tapes exhibits technical characteristics suitable for preparing adhesive handles for heavy packages when high adhesion is required. It is particularly resistant to UV rays.

Technical properties

Backing tape	MOPP
Adhesive	Hot melt
Color	Transparent

Adhesion on steel	15 - 24	N/25 mm	AFERA 5001
Elongation	24 - 32	%	AFERA 5004
Tensile strength	350 - 410	N/25 mm	AFERA 5004
Thickness	49 - 51	µm	AFERA 5006
Total thickness	79 - 81	µm	AFERA 5006

Storage conditions

Recomended temperature	10-40 °C
Humidity	20-80% RH
Shelf life (months)	12

Available sizes

25X6000, 30X5000

Other sizes may be evaluated upon request.

The above mentioned information are extrapolated from typical production data and not constitute a warranty for the results of the applications.

Alimac S.r.l.
Via E. Toti 3,
Gerenzano (VA), Italy

PH: + 39 02 9670 2823
customeroperations.it@alimacgroup.com

Alimac Iberia s.l.u.
C/Travessera de Gracia,
73-79 3º 3ª
08006 ,
Barcelona, Spain
PH: +34 93 2385943
customeroperations.es@alimacgroup.com

Alimac Deutschland GmbH
Am Busskolk 9,
Bocholt, Germany
PH: + 49 (0) 2871 238120
customeroperations.de@alimacgroup.com