

C105 HT

Product description

C105 HT Carry Handle Tapes is the ideal solution for obtaining adhesive handles for transporting heavy and bulky packages. Due to its high adhesion on shrink PE film, it offers special mechanical resistance and inertia to oxidizing agents. Made of MOPP polypropylene material, it is designed to withstand passage through the shrink oven.

Technical properties

Backing tape	MOPP
Adhesive	Hot melt
Color	Transparent

Adhesion on steel	11 - 15	N/25 mm	AFERA 5001
Elongation	24 - 32	%	AFERA 5004
Tensile strength	400 - 480	N/25 mm	AFERA 5004
Thickness	54 - 56	µm	AFERA 5006
Total thickness	74 - 76	µm	AFERA 5006

Storage conditions

Recomended temperature	10-40 °C
Humidity	20-80% RH
Shelf life (months)	12

Available sizes

25X6500

Other sizes may be evaluated upon request.

The above mentioned information are extrapolated from typical production data and not constitute a warranty for the results of the applications.

Alimac S.r.l.
Via E. Toti 3,
Gerenzano (VA), Italy

PH: + 39 02 9670 2823
customeroperations.it@alimacgroup.com

Alimac Iberia s.l.u.
C/Travessera de Gracia,
73-79 3º 3ª 08006 ,
Barcelona, Spain

PH: +34 93 2385943
customeroperations.es@alimacgroup.com

Alimac Deutschland GmbH
Am Busskolk 9,
Bocholt, Germany

PH: + 49 (0) 2871 238120
customeroperations.de@alimacgroup.com