

C12550 FA

Product description

C12550 FA Carry handle Tapes Hot Melt tape shows technical characteristics suitable for adhesive handle preparation for high adhesion or frozen application. The elevated resistance of the PET film against high temperatures permits the use of this adhesive tape in shrink-ovens without deformation or degradation of the product characteristics.

Technical properties

Backing tape	PET
Adhesive	Hot melt
Color	Transparent

Adhesion on steel	22 - 30	N/25 mm	AFERA 5001
Elongation	120 - 150	%	AFERA 5004
Tensile strength	190 - 210	N/25 mm	AFERA 5004
Thickness	49 - 51	µm	AFERA 5006
Total thickness	79 - 81	µm	AFERA 5006

Storage conditions

Recomended temperature	10-40 °C
Humidity	20-80% RH
Shelf life (months)	12

Available sizes

25X6500

Other sizes may be evaluated upon request.

The above mentioned information are extrapolated from typical production data and not constitute a warranty for the results of the applications.

Alimac S.r.l.
Via E. Toti 3,
Gerenzano (VA), Italy

PH: + 39 02 9670 2823
customeroperations.it@alimacgroup.com

Alimac Iberia s.l.u.
C/Travessera de Gracia,
73-79 3º 3ª 08006 ,
Barcelona, Spain

PH: +34 93 2385943
customeroperations.es@alimacgroup.com

Alimac Deutschland GmbH
Am Busskolk 9,
Bocholt, Germany

PH: + 49 (0) 2871 238120
customeroperations.de@alimacgroup.com