

## C105 FA UV

### Product description

C105 FA UV is a handle tape designed for excellent UV resistance .

### Technical properties

|              |             |
|--------------|-------------|
| Backing tape | MOPP        |
| Adhesive     | Hot melt    |
| Color        | Transparent |

|                   |           |         |            |
|-------------------|-----------|---------|------------|
| Adhesion on steel | 21 - 25   | N/25 mm | AFERA 5001 |
| Elongation        | 24 - 32   | %       | AFERA 5004 |
| Tensile strength  | 350 - 410 | N/25 mm | AFERA 5004 |
| Thickness         | 49 - 51   | µm      | AFERA 5006 |
| Total thickness   | 79 - 81   | µm      | AFERA 5006 |

### Storage conditions

|                        |           |
|------------------------|-----------|
| Recomended temperature | 10-40 °C  |
| Humidity               | 20-80% RH |
| Shelf life (months)    | 12        |

### Available sizes

25X6000, 30X5000

*Other sizes may be evaluated upon request.*

*The above mentioned information are extrapolated from typical production data and not constitute a warranty for the results of the applications.*

**Alimac S.r.l.**  
Via E. Toti 3,  
Gerenzano (VA), Italy

PH: + 39 02 9670 2823  
[customeroperations.it@alimacgroup.com](mailto:customeroperations.it@alimacgroup.com)

**Alimac Iberia s.l.u.**  
C/Travessera de Gracia,  
73-79 3º 3ª 08006 ,  
Barcelona, Spain

PH: +34 93 2385943  
[customeroperations.es@alimacgroup.com](mailto:customeroperations.es@alimacgroup.com)

**Alimac Deutschland GmbH**  
Am Busskolk 9,  
Bocholt, Germany

PH: + 49 (0) 2871 238120  
[customeroperations.de@alimacgroup.com](mailto:customeroperations.de@alimacgroup.com)