

## C105 HL

### Product description

C105 HL is a prelaminated handle tape designed for general purpose carry applications .

### Technical properties

|                   |                         |
|-------------------|-------------------------|
| Backing tape      | MOPP                    |
| Adhesive          | Hot melt                |
| Color             | Transparent             |
| Available inserts | MOPP, Paper, PE/PP Foam |
| Printing          | 1-8 colors              |

|                   |           |         |            |
|-------------------|-----------|---------|------------|
| Adhesion on steel | 10 - 15   | N/25 mm | AFERA 5001 |
| Elongation        | 24 - 32   | %       | AFERA 5004 |
| Tensile strength  | 350 - 410 | N/25 mm | AFERA 5004 |
| Thickness         | 49 - 51   | µm      | AFERA 5006 |
| Total thickness   | 69 - 71   | µm      | AFERA 5006 |

### Storage conditions

|                        |           |
|------------------------|-----------|
| Recomended temperature | 10-40 °C  |
| Humidity               | 20-80% RH |
| Shelf life (months)    | 12        |

### Available sizes

25X330, 25X3500, 25X5000

Other sizes may be evaluated upon request.

*The above mentioned information are extrapolated from typical production data and not constitute a warranty for the results of the applications.*

**Alimac® S.r.l.**  
Via E. Toti 3,  
Gerenzano (VA), Italy

PH: + 39 02 9670 2823  
[customeroperations.it@alimacgroup.com](mailto:customeroperations.it@alimacgroup.com)

**Alimac® Iberia s.l.u.**  
C/Travessera de Gracia,  
73-79 3º 3ª 08006 ,  
Barcelona, Spain

PH: +34 93 2385943  
[customeroperations.es@alimacgroup.com](mailto:customeroperations.es@alimacgroup.com)

**Alimac® Deutschland GmbH**  
Am Busskolk 9,  
Bocholt, Germany

PH: + 49 (0) 2871 238120  
[customeroperations.de@alimacgroup.com](mailto:customeroperations.de@alimacgroup.com)

[www.alimacgroup.com](http://www.alimacgroup.com)

Revision date: 01/12/25