

C12550 HL

Product description

C12550 HL is a prelaminated handle tape designed for high temperature applications .

Technical properties

Backing tape	PET
Adhesive	Hot melt
Color	Transparent
Available inserts	PET
Printing	1-8 colors

Adhesion on steel	13 - 17	N/25 mm	AFERA 5001
Elongation	120 - 150	%	AFERA 5004
Tensile strength	190 - 210	N/25 mm	AFERA 5004
Thickness	49 - 51	µm	AFERA 5006
Total thickness	69 - 71	µm	AFERA 5006

Storage conditions

Recomended temperature	10-40 °C
Humidity	20-80% RH
Shelf life (months)	12

Available sizes

25X330, 25X3500, 25X5000

Other sizes may be evaluated upon request.

The above mentioned information are extrapolated from typical production data and not constitute a warranty for the results of the applications.

Alimac® S.r.l.
Via E. Toti 3,
Gerenzano (VA), Italy

PH: + 39 02 9670 2823
customeroperations.it@alimacgroup.com

Alimac® Iberia s.l.u.
C/Travessera de Gracia,
73-79 3º 3ª 08006 ,
Barcelona, Spain

PH: +34 93 2385943
customeroperations.es@alimacgroup.com

Alimac® Deutschland GmbH
Am Busskolk 9,
Bocholt, Germany

PH: + 49 (0) 2871 238120
customeroperations.de@alimacgroup.com