

## C105 HL FLEXY



C105 HL FLEXY consists of a transparent adhesive handle with a printable polypropylene insert to meet even the utmost demanding printing specifications.















### TECHNICAL CHARACTERISTICS

Backing type:	<b>MOPP</b>
Thickness:	<b>50 µm</b>
Total thickness:	<b>72 µm</b>
Adhesion on steel:	<b>10 N/25 mm</b>
Adhesion on PE:	<b>5 N/25 mm</b>
Tensile strength:	<b>350 N/25 mm</b>
Elongation:	<b>30%</b>
Label length:	<b>150-400 mm</b>
Handle length:	<b>250-1000 mm</b>
Available colours:	<b>❖Transparent</b>

### INLAY

Backing type	<b>MOPP</b>
Thickness	<b>-</b>
Total thickness	<b>120 µm</b>
Colour	<b>neutral - printed from 1 - 6 colours</b>
Handle length	<b>250 - 1000 mm</b>
Inlay length	<b>150 - 400 mm</b>

### AVAILABLE DIMENSIONS \*

 mm	 m	 mm	 Kg	 cm			 "	 mm	
25	330	< 280	490	120x120x130	12	48	3	25	
25	3500	< 380	430	80x120x170	1	48	6	180	
25	5000	< 380	320	80x120x170	1	24	6	350	
25	7000	< 380	430	80x120x170	1	24	6	350	

\* Other sizes available upon request

### STOCKAGE

Temperature:	10-30°C
Humidity:	40-90%

The above-mentioned data were taken from production samples and are not a warranty for the results of the applications. Therefore each application should be tested in advance.

Limitation of liability: excluding where forbidden by law, Alimac S.r.l. will not be responsible for any loss or damage depending from this Alimac S.r.l. product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to guarantee, contract, negligence or severe responsibility.

The previous guarantee and limited remedy and limitation of responsibility may be changed only by a written agreement signed by authorized officers of Alimac S.r.l. and seller.